



- | | | |
|-------------------|---|----------------|
| 53B - Fast | = | 2 |
| 53 - Slow | = | 1 |
| 31 - Negative | = | Green & Yellow |
| 53A - Positive | = | 3 |
| 31B - Park Return | = | 4 |

SPECIFICATION FOR CLASS 80 DUROWIPER PANTOGRAPH

TRANSFER BOX

- Mild Steel 5mm Box Section
- Powder Coated to:-
- British Engineering Standard 005 Section 22.
- 2 x Inspection Panels (Low Density Polyethylene).
- 2 x 10mm Ball Bearing (Sealed)
- 2 x 10mm Needle Bearings.
- 12 x Oilite Bushes.
- 4 x G Seal Seals (Water Proof Seals).

MOTOR.

- Bosch 24 Volt DC Isolated Earth.
- 5 Amps Starting
- 2 Amps Running.
- Twin Parallel Drive Shafts 12 mm Diameter 316 Stainless Steel
- Distance between shafts 60mm.
- Threaded Spindles M20 x 1mm Pitch Length dependant on Bulkhead thickness and any interfering protrusion.
- Weight :- 8.3 Kilos



DuroWipers
Wiper Manufacturers

This plan and design remain the property of DuroWipers and is loaned on condition that it will not be used against their interest nor reproduced in whole or in part without permission and that it shall be returned if requested.

JURoWipers Unit 20, Oldends Lane Ind.Est., Stonehouse. Gloucestershire. G110 3RQ
Tel: +44(0)844 8541 551- Fax:+44(0)844 8541 550 - sales@durowipers.co.uk - www.durowipers.co.uk

Drawing Number 30807

Tolerances \pm

Material

Quantity

Date 09-05-2006

Drawn by

Project CLASS 80

Customer